



**Town of Mooresville Public Works**  
 4 E. Harrison St. Mooresville, Indiana 46158  
 Telephone 317-831-9547  
**SEWER PERMIT APPLICATION**

Permit #: _____
Issued: _____

<b>Owner:</b>		Telephone:
Mailing Address:		
City:	State:	Zip:
Service Address:		
Lot #:	Subdivision:	
Water Source: Well <input type="checkbox"/> Hill Water <input type="checkbox"/> Indiana American Water <input type="checkbox"/>		

<b>Installer:</b>		Telephone:
Address:		
City:	State:	Zip:
New Installation:		Replacement Line:

**NOTE: Please call by 3:00 P.M. for inspections.**

**Minimum Specifications For Laterals**

1. Pipe size shall be a minimum of 6" unless it is a replacement line, which can be 4".
2. Cleanout must be same size as pipe.
3. Pipe shall be a minimum of 3034 ASTM – bell joint gasket or SDR 35 with glue joints... use schedule 40 under a road or driveway.
4. Bed pipe in 6" of sand if under 12". If over 12", sand or #11 or #8 stone is the only allowable under driveways.
5. Where crossing roads or driveways, the entire trench shall be backfilled with granular backfill.
6. A cleanout must be placed every 100 ft.
7. 90 degree bends are NOT acceptable.
8. 1/8" fall per ft.
9. Keep sewer 10 ft. away from water line.

<b>For Office Use Only</b>			
Plant Improvement Fund:	\$900.00	Sewer Availability Fund:	\$275.00
Developer Availability Fund:	\$825.00	Other:	\$5.00
Clerk's Initials:	Sewer Receipt #	<b>Total:</b>	

Applicant Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Inspector Signature: \_\_\_\_\_ Date: \_\_\_\_\_